

Touret de câble USB 2.0 100m AWG28 AWG24 UL noir

Numéro d'article CU-ROL-100-BK

Longueur 100000mm



Description du produit

Touret de câble USB 2.0, 100m, norme de transmission USB: AWG28/1P (câble à paires "twisted pair", transfert de données) AWG24/2C (connexion 5V), 2x blindé, compatible USB 2.0, diamètre 4,5mm, couleur: noir

Plus d'images



SECTION	ITEM	MATE.	THICK.	DIA.	NOTE	DOUSAGE (kg/km)
A	CONDUCTOR	TINNED COPPER	0.38	70.1275±0.008mm		
28AWG	INSULATION	HD-PE	0.21	±0.05mm COLOR:1.WHITE 2.GREEN		
*1P	EXTRUSION : EXTRUDE					
	TWIST		1.60	S=6543mm		
B	CONDUCTOR	TINNED COPPER	0.61	70.2075±0.008mm		
24AWG	INSULATION	SR-PVC	0.22	±0.05mm COLOR :3.BLACK 4.RED		
*2C	EXTRUSION : EXTRUDE					
	CARLING		2.35	S=5575mm		
	WRAP	ALUMINAR	2.40	COVERAGE:100%		
26AWG	BRAID	TINNED COPPER	0.48	70.1675±0.008mm		
	BRAID	TINNED COPPER	2.80	1640.1075±0.008mm 55%		
	JACKET	PVC	0.85	±0.15mm COLOR: BLACK		
EXTRUSION : IN THE MIDDLE						
	MARKING	HS-SPEED USB Revision 2.0 SHIELDED 28AWG2C-24AWG2C (UL) E305668				
		TYPE CM 75°C CSA 20470 TYPE CM 75°C				
ELECTRICAL CHARACTERISTICS						
CONDUCTOR RESISTANCE AT 20°C: Conductor A: 237.25 Ω/Km max Conductor B: 85.96 Ω/Km max						
MECHANICAL CHARACTERISTICS						
Before Tensile Strength (Mpa): Insulation (SR-PVC): 20.7MPa Jacket :10.3MPa						
Before Aging Elongation (%) : Insulation (SR-PVC): 100% Jacket :100%						
Aging Condition (°C) : Insulation (SR-PVC): 113 ± 1 °C*7days Jacket : 113± 1°C*10days						
After Tensile Strength (Mpa): Insulation (SR-PVC): 70% Jacket : 70%						
After Aging Elongation (%) : Insulation (SR-PVC): 70% Jacket : 65%						
Cold Shock (-20°C/24hrs) : Insulation (SR-PVC): No Crack Jacket :No Crack						
Heat Shock (127°C/14hrs) : Insulation (SR-PVC): No Crack Jacket : No Crack						
SECTION DRAWING:						

