

USB 3.0 HUB concentrateur avec 4 ports boîtier métallique

Numéro d'article EX-1183HMVS-2



Description du produit

USB 3.0 HUB concentrateur avec 4 ports, boîtier métallique, 1x B femelle (entrée) + 4x A femelle (sorties), avec protection de surintensité, câble USB 3.0 et alimentation électrique 3A incl., couleur: noir

Product information

The rugged and industrial grade EX-1183HMVS-2 is a USB 3.2 Gen 1 metal hub for up to four end devices. The hub provides four screwable USB 3.2 Gen 1 downstream ports with 15KV ESD surge protection. It is possible to connect up to four external USB peripherals to one USB 3.2 Gen 1 port from notebook, desktop computer or server in 19" rack. It supports SuperSpeed USB 3.2 Gen 1 data transfer rate of up to 5Gbps and is backward compatible to USB 1.1. The included USB 3.2 Gen 1 cable can be attached to the EX-1183HMVS-2 with thumbscrews without a screwdriver. The EX-1183HMVS-2 can be powered via a DC jack, as well as a two wire terminal block connector (+7V to +48V). The HUB meets the special requirements of industrial applications.

- USB 3.2 Gen 1 Metal HUB with 4 Ports
- 15KV ESD Surge Protection for all 4 Ports
- Protection of Devices against voltage fluctuation
- Power +7V up to +48V DC over the DC-Connector or Terminal Block
- Power supply optionally also from the USB-Bus +5V (Bus-Power)
- Easy installation with the optionally available DIN-Rail Kit
- Automatic recognition the data transfer rate for the attached external devices
- Supports 1,5A power for each output simultaneously
- Support BC v1.2: SDP/CDP/DCP Charging Modes
- Automatic detection of input polarity on the current terminal block
- Rugged Metal Case
- 1x LED Power-Indicator & 4x Status LED

- Category:USB HUB
- Interface:USB 3.2 Gen 1
- Connections: A socket
- Number of ports: 4
- Power connection: DC Jack + TB 7V-48V
- Design: esktop
- Surge protection: 15KV ESD
- Housing: Metal
- Colour: black
- Cable_ screwable
- Cable length meter: 1,5m
- Application: Premium
- Charging power total: 30 W

Plus d'images



