

Adaptateur FireWire 800+400 PCI Express 3 ports

Numéro d'article PX-F84-11



Description du produit

Adaptateur FireWire 800+400 PCI Express 3 ports, www.ioi1394.com FWB-PCIE1X21A

Key Features:

- Host Bus: 1-lane 2.5 Gb/s PCI Express
- Eight (8) isochronous transmit/receive contexts
- Deep 8 Kbyte isochronous transmit/receive FIFOs
- Complies with 1394 OHCI draft 1.2
- Three external 1394 ports
- Bilingual ports with Screw Holes for thumbscrew locking Type 1394b Cable

PCI Express:

- Designed for compliance with PCI Express.
- Multiple virtual channel (VC0,VC1) support for differentiating 1394 isochronous traffic.
- Supports eight user-programmable traffic classes.
- 64-bit and 32-bit platform support.
- Interrupts via legacy INTx interface or message signaled interrupt (MSI).
- Supports PCI Express clock power management via CLKREQN signal for form factors that support this protocol.
- Supports all link power management states (L0,L0s,L1,andL2/L3) and active state power management(ASPM).
- Supports wake-up from a low-power state via in-band beacon signaling and side-band WAKE_N signal.

OHCI (Open Host Controller Interface)

- Enhanced with the OHCI 1.2 draft specification for 1394b-2002 PHY full operational compliance.
- OHCI 1.0 backwards compatible. Configurable via EEPROM to operate in either OHCI 1.0 or OHCI 1.1 mode.
- 8 Kbyte isochronous transmit FIFO.
- 4 Kbyte asynchronous transmit FIFO.
- 8 Kbyte isochronous receive FIFO.
- 8 Kbyte asynchronous receive FIFO.
- Dedicated asynchronous and isochronous descriptor-based DMA engines.
- Eight isochronous transmit contexts.
- Eight isochronous receive contexts.

Supports parallel processing of incoming physical read and write requests.
Supports up to 48-bit addressing per OHCI specification for the physical DMA transfers.

1394b-2002 Link

Cycle master and isochronous resource manager capable.
Supports 1394a-2000 and 1394b-2002 acceleration features.

1394b-2002 PHY

Provides three IEEE 1394b-2002 compliant ports supporting 1394b-2002 speeds of 800 Mbits/s and 400Mbits/s while maintaining backward compatibility to IEEE 1394a-2000 speeds of 100 Mbits/s, 200Mbits/s, and 400 Mbits/s over 4.5 m copper. Fully supports provisions of IEEE 1394a-2000 and 1394-1995 standards for high-performance serial bus. Link is not required for hub operation.
Supports extended BIAS_HANDSHAKE time for enhanced interoperability with camcorders.
Does not require external filter capacitor for PLL.
Supports arbitrated short bus reset to improve utilization of the bus.
Supports ack-accelerated arbitration and fly-by concatenation.
Supports PHY pinging and remote PHY access packets.
Fully supports suspend/resume.
Reports cable power fail interrupt when voltage at CPS ball falls below 7.5 V.

Number of Ports:

Two Bilingual ports with Screw Holes for thumbscrew locking Type 1394b Cable+ One Firewire 1394a Cable Port

Bus Power Connector:

Big IDE 4-pin DC Power Connector

Plus d'images

