

Câble USB 2.0 avec des lignes de 5V épaisses, PREMIUM+ avec noyau de ferrite, 3m

Numéro d'article CU-2820-F-30

Longueur 3000mm



Description du produit

Câble USB 2.0, 3m, très haute qualité AWG28/1P et AWG20/2C avec 1x noyau de ferrite, connectique: USB à 4 broches type A (mâle) - USB à 4 broches type B (mâle), certifié (avec n° TID), noir

Key Features

- USB 2.0 cable
- PREMIUM+ quality
- Length: 3 metres | 3m
- thicker power strands than standard cables (AWG20, CU)
- Double shielding
- 1 ferrite core
- certified (with TID number, e.g. TID 60000467)
- W
- wire gauges: 20AWG/2C 28AWG/1P
- conductor material: pure copper (CU)
- data cables twisted twisted pair
- cable diameter approx. Ø 5mm
- shielded connectors with 30µ gold-plated contacts
- connector types A/B according to USB standard
- USB 2.0 High Speed, downward compatible with USB 1.1
- Suitable for 480 MBit/s (high speed), 12 MBit/s (full speed) and 1.5 MBit/s (low speed)
- cable imprint: HI-SPEED USB Revision 2.0 SHIELDED 28AWG/1P+20AWG/2C VW-1 80°C 30V
- colour: black
- customs tariff no.: 85444290, Made in PRC
- CE, WEEE, RoHS compliant

Plus d'images



